







**Rigid PVC smooth tubes with flared union.**

## Uses

Suitable for surface mounting to protect the electric conductors.

## Characteristics

Colours	 <b>Grey RAL 7035 or black</b>	Compressive strength	 <b>Strong: 1250N</b>
Fire behaviour	 <b>Non flame propagation</b>	Bending resistance	 <b>Rigid (pliable when hot)</b>
Dimensions	 <b>UNE-EN 60423</b>	Impact resistance	 <b>Middle: 2J</b>
Packing	 <b>Bundles of 3 m. bars, in pallets</b>	Maximum temperature	 <b>60°C</b>
Standard	 <b>UNE-EN 61386-21</b>	Minimum temperature	 <b>-5°C</b>
Electrical properties	 <b>Insulating</b>		

## Technical data

Nominal	Ref.	Descripción	Embalaje mts	Pallet mts	Diámetro exterior mm	Diámetro interior aproximado mm
16	T20216G6	BLINDADO ABOCARDADO 16 GRIS	57	2565	16 +0/-0,3	10.7
20	T20220G6	BLINDADO ABOCARDADO 20 GRIS	57	3420	20 +0/-0,3	14.1
25	T20225G6	BLINDADO ABOCARDADO 25 GRIS	57	2052	25 +0/-0,4	18.3
32	T20232G6	BLINDADO ABOCARDADO 32 GRIS	30	1350	32 +0/-0,4	25.3
40	T20240G6	BLINDADO ABOCARDADO 40 GRIS	30	840	40 +0/-0,4	31.2
50	T20250G6	BLINDADO ABOCARDADO 50 GRIS	15	600	50 +0/-0,5	39.6
63	T20263G6	BLINDADO ABOCARDADO 63 GRIS	15	360	63 +0/-0,6	52.6
16	T20216N6	BLINDADO ABOCARDADO 16 NEGRO	57	2565	16 +0/-0,3	10.7
20	T20220N6	BLINDADO ABOCARDADO 20 NEGRO	57	3420	20 +0/-0,3	14.1
25	T20225N6	BLINDADO ABOCARDADO 25 NEGRO	57	2052	25 +0/-0,4	18.3
32	T20232N6	BLINDADO ABOCARDADO 32 NEGRO	30	1350	32 +0/-0,4	25.3
40	T20240N6	BLINDADO ABOCARDADO 40 NEGRO	30	840	40 +0/-0,4	31.2
50	T20250N6	BLINDADO ABOCARDADO 50 NEGRO	15	600	50 +0/-0,5	39.6
63	T20263N6	BLINDADO ABOCARDADO 63 NEGRO	15	360	63 +0/-0,6	52.6