



## Tube Special tubes **CORRUGATED 750**

revi@grupo-revi.com

+34 988 215 454

grupo-revi.com













**Corrugated PVC tubes for electrical installations with a compressive strength of 750 Newton and incorporated guideway.**

### Uses

Suitable for flush mounting on walls and ceilings to protect the electric conductors.

### Characteristics

Fire behaviour	 <b>No propagador de la llama</b>
Dimensions	 <b>UNE-EN 60423</b>
Packing	 <b>Rollos de 100m para 16 y 20, 75m para 25, 50 para 32 y 35 para 40, 50 y 63</b>
Standard	 <b>UNE-EN 61386-22</b>
Electrical properties	 <b>No declaradas</b>
Compressive strength	 <b>750N</b>
Bending resistance	 <b>Curvable</b>
Impact resistance	 <b>2J</b>
Maximum temperature	 <b>60°C</b>
Minimum temperature	 <b>-5°C</b>

### Technical data

Diámetro nominal	Diámetro exterior mm	Tolerancias mm	Diámetro interior aproximado mm
16	16	+0/-0,3	10.7
20	20	+0/-0,3	14.1
25	25	+0/-0,4	18.3
32	32	+0/-0,4	25.3
40	40	+0/-0,4	31.2
50	50	+0/-0,5	39.6
63	63	+0/-0,6	52.6