



Corrugated PVC tubes for electrical installations with a compressive strength of 750 Newton and incorporated guideway.

Uses

Suitable for flush mounting on walls and ceilings to protect the electric conductors.

Characteristics

Fire behaviour	No propagador de la llama	Compressive strength	750N
Dimensions	UNE-EN 60423	Bending resistance	Curvable
Packing	Rollos de 100m para 16 y 20, 75m para 25, 50 para 32 y 35 para 40, 50 y 63	Impact resistance	2J
Standard	UNE-EN 61386-22	Maximum temperature	60°C
Electrical properties	No declaradas	Minimum temperature	-5°C

Technical data

Nominal	Código	Descripción	Embalaje mts	Pallet mts	Diámetro exterior mm	Diámetro interior aproximado mm
16	T11015G4	CORRUGADO 750 M-16 GRIS	100	6000	16 +0/-0,3	10.7
20	T11020G4	CORRUGADO 750 M-20 GRIS	100	5200	20 +0/-0,3	14.1
25	T11025G3	CORRUGADO 750 M-25 GRIS	75	3300	25 +0/-0,4	18.3
32	T11032G2	CORRUGADO 750 M-32 GRIS	50	2200	32 +0/-0,4	25.3
40	T11040G1	CORRUGADO 750 M-40 GRIS	25	1100	40 +0/-0,4	31.2
50	T11050G1	CORRUGADO 750 M-50 GRIS	25	900	50 +0/-0,5	39.6