



**Corrugated PVC tubes for electrical installations with a compressive strength of 750 Newton and incorporated guideway.**

## Uses

Suitable for flush mounting on walls and ceilings to protect the electric conductors.

## Characteristics

Fire behaviour	<b>No propagador de la llama</b>	Compressive strength	<b>750N</b>
Dimensions	<b>UNE-EN 60423</b>	Bending resistance	<b>Curvable</b>
Packing	<b>Rollos de 100m para 16 y 20, 75m para 25, 50 para 32 y 35 para 40, 50 y 63</b>	Impact resistance	<b>2J</b>
Standard	<b>UNE-EN 61386-22</b>	Maximum temperature	<b>60°C</b>
Electrical properties	<b>No declaradas</b>	Minimum temperature	<b>-5°C</b>

## Technical data

Nominal	Código	Descripción	Embalaje mts	Pallet mts	Diámetro exterior mm	Diámetro interior aproximado mm
16	T11015G4	CORRUGADO 750 M-16 GRIS	100	6000	16 +0/-0,3	10.7
20	T11020G4	CORRUGADO 750 M-20 GRIS	100	5200	20 +0/-0,3	14.1
25	T11025G3	CORRUGADO 750 M-25 GRIS	75	3300	25 +0/-0,4	18.3
32	T11032G2	CORRUGADO 750 M-32 GRIS	50	2200	32 +0/-0,4	25.3
40	T11040G1	CORRUGADO 750 M-40 GRIS	25	1100	40 +0/-0,4	31.2
50	T11050G1	CORRUGADO 750 M-50 GRIS	25	900	50 +0/-0,5	39.6