



Double-walled pipes with corrugated outer layer made of PE with the necessary additives to resist ultraviolet radiation from sunlight.

Uses

Suitable for installation buried directly in the ground without additional protection. Indicated for the installation of electrical networks, telecommunication lines, water pipes, gas pipes, etc.

Suitable for photovoltaic installations both in the underground section and in the exits to the outside.

Characteristics

Colours	Black	Standard	UNE-EN 61386-24
Conductor	Copper	Compressive strength	450 N
Dimensions	UNE-EN 61386-24	UV resistance	The resistance to ultraviolet radiation of these tubes has been checked by means of an additional test to the AENOR brand certification. This test is the one prescribed in the UNE 21123 standard for 0.6/1KV cables and is carried out in accordance with the UNE 211605:2013 standard.
Packing	Rolls	Impact resistance	15 J for 40 and 50, 20 J for 63, 75 and 90, 28 J for 110 and 125 and 40 J for 160, 200

Technical data

Diámetro nominal mm	Diámetro exterior mm	Tolerancias mm	Diámetro interior mínimo mm
40	40	+0,8	30
50	50	+1	37
63	63	+1,2	47
75	75	+1,4	56
90	90	+1,7	67
110	110	+2	82
125	125	+2,3	94
160	160	+2,9	120
200	200	+3,6	150