

**Double layer tubes with the inner layer in corrugated rigid PVC and the outer in flexible PVC.**

## Uses

Suitable for flush wall and ceiling mounting to protect the electric conductors.

## Characteristics

|                       |  |                      |                |
|-----------------------|--|----------------------|----------------|
| Fire behaviour        | <b>Non flame propagation</b>   | Compressive strength | <b>320N</b>    |
| Dimensions            | <b>UNE-EN 60423</b>  | Bending resistance   | <b>Pliable</b> |
| Packing               | <b>100 m. rolls for 16 and 20; 75 m. for 25; 50 m. For 32; and 25 m. For 40, 50 and 63</b> | Impact resistance    | <b>2J</b>      |
| Standard              | <b>UNE-EN 61386-22</b>   | Maximum temperature  | <b>60°C</b>    |
| Electrical properties | <b>Insulating</b>  | Minimum temperature  | <b>-5°C</b>    |

## Technical data

| Codigo   | Rollo mts | Pallet mts | Diámetro nominal | Diámetro exterior aproximado mm | Diámetro interior aproximado mm |
|----------|-----------|------------|------------------|---------------------------------|---------------------------------|
| T10215N4 | 100       | 6000       | 16               | 16                              | 10.7                            |
| T10220N4 | 100       | 5200       | 20               | 20                              | 14.1                            |
| T10225N3 | 75        | 3300       | 25               | 25                              | 18.3                            |
| T10232N2 | 50        | 2200       | 32               | 32                              | 25.3                            |
| T10240N2 | 25        | 1100       | 40               | 40                              | 31.2                            |
| T10250N1 | 25        | 900        | 50               | 50                              | 39.6                            |