PVC CONDUIT

revi@grupo-revi.com
+34 988 215 454
grupo-revi.com



Non metalic rigid conduit with internal an external plain wall. This pipe is make with rigid PVC, 1250N (4422) and 750N (3322)

Uses

Suitable for the conduction of electrical cables in visible installations, due to its good characteristics in terms of resistance to compression, impact, dielectric strength and insulation resistance.

Characteristics

Colours	**Orange**	Compressive strength	**1250 ó 750 N**
Fire behaviour	**No propagator of the flame**	Bending resistance	**Rigid**
Dimensions	**16, 20, 25, 32, 40, 50 Y 63 mm**	Impact resistance	**6 J**
Level of protection	**IP 54**	Maximum temperature	**+ 90 °C**
Standard	**IEC 61386-21**	Minimum temperature	**-5 °C**
Electrical properties	**Insulating**	Connection	**By flared**

Technical data

Nominal Diameter mm	External Diameter mm	Diameter mm	Minumum Inside Diameter mm	Minimum entry lenght mm
16	16	-0/+0,3	10.7	16
20	20	-0/+0,3	14.1	20
25	25	-0/+0,3	18.3	25
32	32	-0/+0,3	25.3	30
40	40	-0/+0,3	31.2	32
50	50	-0/+0,3	39.6	42
63	63	-0/+0,3	52.6	50