



Bends with flared ends.
Bends with threaded ends.
Threaded couplings.

Uses

Suitable for unions of armoured rigid tubes

Characteristics

| | | | |
|----------------|--|-----------------------|--|
| Colours | Grey RAL 7035 and black | Level of protection | IP54 (Contra salpicaduras de agua y contra polvo) |
| Fire behaviour | Non flame propagation | Standard | UNE-EN 61386-2-1 |
| Dimensions | UNE-EN 61386-2-1 and UNE-EN 60423 | Electrical properties | Insulating |
| Packing | Carton boxes | Impact resistance | Middle (2J) |

Technical data

| Díámetro | Rosca externa L mínima mm | Rosca interna L máxima mm | Enchufable D max entrada mm | Enchufable L mínima entrada mm |
|----------|---------------------------|---------------------------|-----------------------------|--------------------------------|
| 16 | 12.5 | 13.5 | 16.5 | 16 |
| 20 | 14 | 15 | 20.5 | 20 |
| 25 | 17 | 18 | 25.5 | 25 |
| 32 | 19 | 20 | 32.6 | 30 |
| 40 | 19 | 20 | 40.7 | 32 |
| 50 | 19 | 20 | 50.8 | 42 |
| 63 | 19 | 20 | 63.9 | 50 |