



Flexible single core non-sheathed cables, insulated with thermoplastic compound, and low emission of smoke and corrosive gases.

Uses

Specially recommended for the internal wiring of devices placed in public attendance space

Characteristics

Insulation	PVC T17 according to UNE-EN-50363-7	Sections	2.5 a 240 mm²
Colours	Yellow-green, orange, red, rose, violet, turquoise, blue, black, white, grey and brown	Temperature	70°C
Conductor	Copper class 5 according to UNE-EN 60228	Test voltage	2500V
Packing	1.5 200 m. laminated rolls; for the other sections, 100 m. rolls	Rated voltage	450/750V
Standard	UNE 21002		

Technical data

Sección mm ²	Espesor mm	Diámetro mm	Resistencia a 20 °C Ohm/km	Peso aprox. Kg/Km
1.5	0.7	3	13.3	19
2.5	0.8	3.6	7.98	31
4	0.8	4.2	4.95	47
6	0.8	4.8	3.3	70
10	1	6.25	1.91	120
16	1	7.3	1.21	190
25	1.2	9.1	0.78	297
35	1.2	10.3	0.554	400
50	1.4	12.65	0.386	560
70	1.4	14.1	0.272	785
95	1.6	16.4	0.206	1025
120	1.6	18.75	0.161	1150