



**Rigid single core non-sheathed cables, with thermoplastic compound insulation having low emissions of smoke and corrosive gases.**

## Uses

Specially recommended for the installations described in the "technical additional instru

## Characteristics

Insulation	<b>TI7 according to UNE-EN 50363-7</b>	Sections	<b>1.5 a 240 mm 2</b>
Colours	<b>Yellow-green, orange, red, rose, violet, turquoise, blue, black, grey, and brown</b>	Temperature	<b>70°C</b>
Conductor	<b>Copper class 2 according to UNE-EN 60228</b>	Test voltage	<b>2500V</b>
Packing	<b>1.5 200 m. laminated rolls, and 100 m. rolls the other sections.</b>	Rated voltage	<b>450/750V</b>
Standard	<b>UNE 21002</b>		

## Technical data

Sección mm2	Espesor mm	Diámetro mm	Resistencia a 20 °C Ohm/km	Peso aprox. Kg/Km
1.5	0.7	2.8	12.1	20
2.5	0.8	3.4	7.41	31
4	0.8	3.9	4.61	47
6	0.8	4.75	3.08	69
10	1	5.8	1.83	121
16	1	6.75	1.15	175
25	1.2	8.45	0.727	275
35	1.2	9.5	0.524	378
50	1.4	11.3	0.387	510
70	1.4	12.75	0.268	704