



Multipolar cables with flexible conductor, PVC insulation and PVC sheath.

Uses

Installation in domestic premises, kitchens and offices. For lightweight portable devices. These cables are for small mechanical stresses (for example for radio sets, table lamps, hanging lamps and office machines)

Characteristics

Insulation	PVC T2 according to EN 50363-3	Standard	UNE EN 50525-2-11
Colours	White, grey or black	Sections	2, 3, 4, 5 x 0.75 a 4 mm²
Conductor	Copper class 5 according to UNE-EN 60228	Temperature	70°C
Sheath	PVC TM2 according to EN 50363-4-1	Test voltage	2000V
Packing	Laminated rolls	Rated voltage	300/300V
Single pole identification	By color according to UNE 21089-1		

Technical data

Sección mm ²	Espesor aislamiento mm	Espesor cubierta mm	Diámetro mm	Resistencia a 20 °C Ohm/Km
2x0,5	0.5	0.6	4,6-5,9	39
2x0,75	0.5	0.6	4,9-6,3	26
3x0,5	0.5	0.6	4,9-6,3	39
3x0,75	0.5	0.6	5,2-6,7	26
4x0,5	0.5	0.6	5,4-6,9	39
4x0,75	0.5	0.6	5,7-7,3	26