












**H05VV-F****PVC insulated and PVC sheathed flexible multipolar cables.****Uses**

Installation in household rooms, kitchens and offices. For domestic devices, even those placed in humid spots. To be used under mean mechanical stress (for exam

Characteristics

| | |
|----------------------------|---|
| Insulation |  PVC T17 according to UNE-21031 |
| Colours |  White, grey or black |
| Conductor |  Copper class 5 according to UNE-EN 60228 |
| Packing |  100 m. laminated rolls |
| Single pole identification |  By situation according to UNE 21089-1 |
| Standard |  UNE 21031 |
| Sections |  2, 3, 4, 5 x 0.75 a 4 mm² |
| Temperature |  70°C |
| Test voltage |  2000V |
| Rated voltage |  300/500V |

Technical data

| Sección mm ² | Espesor aislamiento | | Diámetro mm | Resistencia a 20 °C Ohm/Km |
|-------------------------|---------------------|------------------------|-------------|-------------------------------|
| | mm | Espesor cubierta mm | | |
| 2x0,75 | 0,6 | 0,8 | 6,3 | 26 |
| 2x1 | 0,6 | 0,8 | 6,65 | 19,5 |
| 2x1,5 | 0,7 | 0,8 | 7,6 | 13,3 |
| 2x2,5 | 0,8 | 1 | 9,3 | 7,98 |
| 2x4 | 0,8 | 1,1 | 10,5 | 4,95 |
| 3G0,75 | 0,6 | 0,8 | 6,65 | 26 |
| 3G1 | 0,6 | 0,8 | 7,1 | 19,5 |
| 3G1,5 | 0,7 | 0,9 | 8,2 | 13,3 |
| 3G2,5 | 0,8 | 1,1 | 10,5 | 7,98 |
| 3G4 | 0,8 | 1,2 | 11,05 | 4,95 |
| 4G0,75 | 0,6 | 0,8 | 7,6 | 26 |
| 4G1 | 0,6 | 0,9 | 7,95 | 19,5 |
| 4G1,5 | 0,7 | 1 | 9,25 | 13,3 |
| 4G2,5 | 0,8 | 1,1 | 11,05 | 7,98 |
| 4G4 | 0,8 | 1,2 | 12,75 | 4,95 |

| | | | | |
|--------|-----|-----|-------|------|
| 5G0,75 | 0,6 | 0,9 | 8 | 26 |
| 5G1 | 0,6 | 0,9 | 9 | 19,5 |
| 5G1,5 | 0,7 | 1,1 | 11,05 | 13,3 |
| 5G2,5 | 0,8 | 1,2 | 13,2 | 7,98 |
| 5G4 | 0,8 | 1,4 | 15,4 | 4,95 |