












PVC insulated and PVC sheathed flexible multipolar cables.

Uses

Installation in domestic premises, kitchens and offices. For domestic appliances, even those in damp places. These cables are for medium mechanical stress (for example for washing machines, centrifuges and refrigerators)

Characteristics

Insulation	 PVC T12 according to EN 50363-3	Standard	 UNE EN 50525-2-11
Colours	 White, grey or black	Sections	 2, 3, 4, 5 x 0.75 a 4 mm²
Conductor	 Copper class 5 according to UNE-EN 60228	Temperature	 70°C
Sheath	 PVC TM2 according to EN 50363-4-1	Test voltage	 2000V
Packing	 Laminated rolls	Rated voltage	 300/500V
Single pole identification	 By color according to UNE 21089-1		

Technical data

Sección mm ²	Espesor aislamiento mm	Espesor cubierta mm	Diámetro mm	Resistencia a 20 °C Ohm/Km
2x0,75	0.6	0.8	6.3	26
2x1	0.6	0.8	6.65	19.5
2x1,5	0.7	0.8	7.6	13.3
2x2,5	0.8	1	9.3	7.98
2x4	0.8	1.1	10.5	4.95
3G0,75	0.6	0.8	6.65	26
3G1	0.6	0.8	7.1	19.5
3G1,5	0.7	0.9	8.2	13.3
3G2,5	0.8	1.1	10.5	7.98
3G4	0.8	1.2	11.05	4.95
4G0,75	0.6	0.8	7.6	26
4G1	0.6	0.9	7.95	19.5
4G1,5	0.7	1	9.25	13.3
4G2,5	0.8	1.1	11.05	7.98
4G4	0.8	1.2	12.75	4.95
5G0,75	0.6	0.9	8	26
5G1	0.6	0.9	9	19.5
5G1,5	0.7	1.1	11.05	13.3
5G2,5	0.8	1.2	13.2	7.98
5G4	0.8	1.4	15.4	4.95