



Flexible PVC insulated single core non-sheathed cables.

Uses

To be installed in surface mounted conducts, flush mounted, and similar closed systems.

Characteristics

Insulation	PVC T11 according to UNE-21031	Sections	1.5 a 95mm 2
Colours	Yellow-green, orange, red, rose, violet, turquoise, blue, black, white, grey and brown	Temperature	70°C
Conductor	Copper class 5 according to UNE-EN 60228	Test voltage	2500V
Packing	1.5 in 200 m. laminated rolls; the other sections in 100 m. rolls	Rated voltage	450/750V
Standard	UNE 21031		

Technical data

Sección mm2	Código	Descripción	Espesor mm	Diámetro mm	Resistencia a 20 °C Ohm/km	Peso aprox. Kg/Km
1.5	T4201005x5	H07V-K 1x1,5 CPR	0.7	3	13.3	19
2.5	T4201007x0	H07V-K 1x2,5 CPR	0.8	3.6	7.98	31
4	T4201009x0	H07V-K 1x4 CPR	0.8	4.2	4.95	47
6	T4201011x0	H07V-K 1x6 CPR	0.8	4.8	3.3	70
10	T4201012x0	H07V-K 1x10 CPR	1	6.25	1.91	120
16	T4201013x0	H07V-K 1x16 CPR	1	7.3	1.21	190
25	T4201014x0	H07V-K 1x25 CPR	1.2	9.1	0.78	297
35	T4201015x0	H07V-K 1x35 CPR	1.2	10.3	0.554	400
50	T4201016x0	H07V-K 1x50 CPR	1.4	12.65	0.386	560
70	T4201016x0	H07V-K 1x70 CPR	1.4	14.1	0.272	785
95	T4201017x0	H07V-K 1x90 CPR	1.6	16.4	0.206	1025