



Rigid insulated non-sheathed cabled assembly with copper conductor and cross-linked polyethylene (XLPE) insulated.

Uses Suitable for distribution lines, connections and the like. Suitable for lean-on installations. If a suspen

Characteristics

Insulation		Cross-linked polyethylene according to UNE 21030
Clasificación CPR		Fca
Colours		Black
Conductor		Copper class 2 according to UNE-EN 60228
Packing		Reels
Standard		UNE 21030-2
Sections		2, 3, 4 x 2.5 a 25 mm²
Temperature		90°C
Test voltage		4000V
Rated voltage		0.6/1kV

Technical data

Seccion mm ²	Espesor aislamiento mm	Diametro mm	Resistencia a 20 °C Ohm/km
2x2,5	1.2	8.4	7.41
2x4	1.2	9.3	4.61
2x6	1.2	11.1	3.08
2x10	1.2	12.4	1.83
2x16	1.2	14.2	1.15
2x25	1.4	17.4	0.727
3x2,5	1.2	9.1	7.41
3x4	1.2	10.1	4.61
3x6	1.2	12	3.08
3x10	1.2	13.4	1.83
3x16	1.2	15.4	1.15
3x25	1.4	18.8	0.727
4x2,5	1.2	10.2	7.41
4x4	1.2	11.3	4.61
4x6	1.2	13.4	3.08

4x10	1.2	15	1.83
4x16	1.2	17.2	1.15
4x25	1.4	21.1	0.727